$\mathcal{Shelly}$®2.5

Completely re-engineered, 100% Protected

Shelly 2.5 Wi-Fi dual relay switch with dual power metering is 20% more powerful, 30% smaller and with 50% range increased than his predecessor.

Power supply

110-230V ±10, 50/60Hz AC and 24-60V DC Shelly 2.5 is compatible with all major international voltage standards.

Wireless 802.11 b/g/n

Shelly 2.5 can connect directly to any Wi-Fi network, no HUB required or can operate as an Access Point.

Maximum load per output

10A / 230V 50/60Hz. You can control a wide range of home appliances and office equipment

Weekly schedules

Choose a time and create custom daily schedules for your devices.

Dual power metering

Shelly 2.5 has an integrated precise dual power meter. You can measure the independent consumption for each channel.

Overheating protection

Internal temperature sensor for overheating protection

Double relay switch & roller shutter functionality

Shelly 2.5 is multifunctional. You can easily switch between these 2 modes and control 2 independent electric circuits or a 3-wire motor.

Embedded web server

You can control any electrical equipment up to 10A per channel. Thus you can control a wide range of home appliances and office equipment.

Shelly mobile app control

Turn devices on/off directly from your smartphone or tablet. You can control lightning, heating and any other connected electrical appliance in your house.

Sunrise/sunset shedules

Shelly 2.5 can automatically turn on/off based on the sunrise and sunset hours

www.home2link.nl/shelly25

Home2Link | Tingietersweg 107, 2031 ER, HAARLEM | 085-0290578 | info@home2link.nl