FIBARO | Walli N Outlet type E

Model: FGWSONE-011

Single high quality power outlet equipped with one socket type E . Max load current is 16A.







PRODUCT HIGHLIGHTS

- Easy assembly in a standard electrical box.
- Perfect match with the mechanism and assembly in multiple frames with other products in the Walli line.

FIBARO | Walli N Outlet type E

TECHNICAL DATA

Power Supply	110-230V~ 50/60 Hz
Recommended wires	1.5-4.0mm2
For installation in boxes	Ø = 60mm depth ≥ 50mm
Operating temperature	0-40 °C
Ambient humidity	10-90% RH without condensation
Rated load	current 16A - resistive loads
Number of outputs	1
Dimensions (Length x Width x Height)	45 x 86 x 86 mm

PACKAGING GIFT PACK

Weight	0.162 kg
Length	11.5 cm
Width	7.5 cm
Height	14 cm
Pieces	1

PACKAGING INNER CARTON

Weight	13 kg
Length	43 cm
Width	56 cm
Height	37 cm
Pieces	63

FIBARO | Walli N Outlet type F

Model: FGWSONF-011

Single high quality power outlet equipped with one socket type F. Max load current is 16A.







PRODUCT HIGHLIGHTS

- Easy assembly in a standard electrical box.
- Perfect match with the mechanism and assembly in multiple frames with other products in the Walli line.

FIBARO | Walli N Outlet type F

TECHNICAL DATA

Power Supply	110-230V~ 50/60 Hz
Recommended wires	1.5-4.0mm2
For installation in boxes	Ø = 60mm depth ≥ 50mm
Operating temperature	0-40 °C
Ambient humidity	10-90% RH without condensation
Rated load	current 16A - resistive loads
Number of outputs	1
Dimensions (Length x Width x Height)	45 x 86 x 86 mm

PACKAGING GIFT PACK

Weight	0.163 kg
Length	11.5 cm
Width	7.5 cm
Height	14 cm
Pieces	1

PACKAGING INNER CARTON

Weight	13 kg
Length	43 cm
Width	56 cm
Height	37 cm
Pieces	63