

## Homebridge Plugin Shelly;

### Homebridge-Shelly;

#### Supported devices;

<ul style="list-style-type: none"> <li>• Shelly 1</li> <li>• Shelly 1L</li> <li>• Shelly 1PM</li> <li>• Shelly 2 <sup>1</sup></li> <li>• Shelly 2.5 <sup>1</sup></li> <li>• Shelly 3EM</li> <li>• Shelly 4Pro</li> <li>• Shelly Air</li> <li>• Shelly Bulb <sup>2</sup></li> <li>• Shelly Button 1 <sup>3</sup></li> </ul>	<ul style="list-style-type: none"> <li>• Shelly Dimmer</li> <li>• Shelly Dimmer 2</li> <li>• Shelly Door/Window</li> <li>• Shelly Door/Window 2 <sup>3</sup></li> <li>• Shelly Duo</li> <li>• Shelly EM</li> <li>• Shelly Flood</li> <li>• Shelly HD</li> <li>• Shelly H&amp;T</li> </ul>	<ul style="list-style-type: none"> <li>• Shelly i3</li> <li>• Shelly Motion <sup>4</sup></li> <li>• Shelly Plug</li> <li>• Shelly Plug S</li> <li>• Shelly Plug US</li> <li>• Shelly RGBW2</li> <li>• Shelly Sense</li> <li>• Shelly Uni</li> <li>• Shelly Vintage</li> </ul>
--	---	---

### Notes

<sup>1</sup> To use Shelly 2 or Shelly 2.5 in roller shutter mode the device must have been calibrated and be running firmware version 1.4.9 or later.

<sup>2</sup> Requires firmware version 1.5.1 or later.

<sup>3</sup> Requires firmware version 1.8.0 or later.

<sup>4</sup> Requires setting the Internet & Security -> CoIoT -> Remote address option on the Shelly device to the IP address of your device running homebridge.

## Homebridge-Shelly-Ng (next Generation);

### Supported devices;

<ul style="list-style-type: none"><li>• Shelly Plus 1</li><li>• Shelly Plus 1 PM</li><li>• Shelly Plus 2 PM <sup>1</sup></li><li>• Shelly Plus I4</li></ul>	<ul style="list-style-type: none"><li>• Shelly Plus Plug US</li><li>• Shelly Pro 1</li><li>• Shelly Pro 1 PM</li><li>• Shelly Pro 2</li></ul>	<ul style="list-style-type: none"><li>• Shelly Pro 2 PM</li><li>• Shelly Pro 3</li><li>• Shelly Pro 4 PM</li></ul>
---	---	--

### Notes

<sup>1</sup> To use Shelly Plus 2PM in Cover mode the device must have been calibrated.

Home2Link