

Click the device to enjoy its intelligent control for home automation.



### Product Specifications

Product Name	Zigbee Temperature Humidity Sensor
Battery specification	CR2032 button cell
Wireless protocol	Zigbee
Temperature measurement range	-10°C~50°C
Humidity measurement range	0%-99%RH
Working voltage	DC2.4V-3V
Product size	ф60×16.7mm/16.7×60×60mm
Screen size	ф46.5mm/46.5×46.5mm
Product net weight	42g/49.5g

1. During the free warranty period, if the product breaks down during normal use, we will offer free maintenance for the product.
2. Natural disasters/man-made equipment failures, disassembly and repair without the permission of our company, no warranty card, products beyond the free warranty card, care not within the scope of the permission of the pe

### RECYCLING INFORMATION

## FCC Statement

FCC Statement

Federal Communication Commission Interference
Statement
This equipment has been tested and found to comply with the
This equipment has been tested and found to comply with the
FCC Rules. These limits and designed to provide reasonable
protection against harmful interference in a residential
residential the requipment generates, uses, and can relate
residential the requipment generates, uses, and can relate
residential residence of the residence o

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Radiation Exposure Statement
This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.

Product Info			
Product Nan	10		
Product Type	9		
Purchase da	te		
Warranty Per	riod		
Dealer Inform	nation		
Customer's I	Vame		
Customer Ph	none		
Customer Ac	idress		
Maintenance F	lecords		
Failure date	Cause Of Issue	Fault Content	Principal













rigesason from the light exale 🔘 **%88 %88** \$.88F

Zigbee Temperature Humidity Instruction Manual









请扫描二维码获取中文说明

### Table Place Mode





### Hanging Mode

### Wall-mounting Mode

Peel of the wall sticker release paper and stick one side of the wall sticker to the adhesive area on the back of the product; after removing the other side of the release paper, stick the product on the indoor wall.



# Maintenance and Care

Battery Replacement

Open the back cover from the bottom of the body, put a model CR2032 positive button battery up into the battery compartment, and then squeeze it hard against the clasp and snap the back cover closed.

Avoid washing the product with water, and avoid scrubbing with acid and alkaline detergent.

## Packing list

## Product Introduction

Zigbee Temperature Humidity Sensor can sense the temperature of surrounging environment and humidity changes in real time, actively report to the user side, at the same time.

















## Preparation for use

1 Cell phone connected to Zigbee gateway





2 Download and open the APP

Search "Smart Life" in the app store or scan the QR code on the package/ manual to download and install the APP if you are downloading for the first time please click the "Register" button to register your accountif you a



# Zigbee Link/Reset:

- 1. Please pull out the insulator in the Zigbee Hygrometer for normal power on state.



