

Remove the switch and pull it away from the wall. Identify Line/Load Wire(Note:The color of your wire may be different from the color shown on the manual.)

### A Verify power is off

5



 Bitte scannen Sie den QR-Code, um das deutsche Handbuch, das Installationsvideo und die Eurotionseinführung zu erhalten

Escanee el código QR para obtener el manual en español. el video de instalación y la introducción de la función


 Veuillez scanner le code QR pour obtenir le manuel en français, la vidéo d'installation et l'introduction des fonctions

• Отсканируйте QR-код, чтобы получить руководство на русском языке, видео по установке и описание функций

 Leia o código QR para obter o manual em português, o vídeo de instalação e a introdução das funções

Global international operation Whenever & Wherever You are, All-in-one Mobile App





#### Inhouse local operation




# TECHNICAL SPECIFICATIONS

Product Type	Smart Switch Module(Wi-Fi+RF)
Voltage	90-250V AC
Current	10A
Wireless Protocol	Wi-Fi 2.4GHz IEEE 802.11 b/g/
RF Frequency	RF433 MHz
Operation Temp.	-10°C - +40°C
Case Temp.	Tc: +80°C (Max.)
Operation Range	≤200 m
Dims (WxDxH)	52x47x18 mm
IP Rating	IP20

# WIRING DIAGRAM

# 1. With one switch Ν SIL LI L N (\* Light





- Turn off the circuit breaker and use the electrical tester to test the power.
- Ensure the circuit breaker is off before wiring.



#### Attention:

## 2. Without switch






## INSTALLATION


#### A Warnings:

1. Installation must be carried out by a qualified electrician in accordance with local regulations.

2. Keep the device out of the reach of children.

- 3. Keep the device away from water, damp or hot environment.
- 4. Install the device away from strong signal sources such as microwave oven that may cause signal interruption resulted in abnormal operation of the device
- 5. Obstruction by concrete wall or metallic materials may reduce the effective operation range of the device and should be avoided.
- 6. Do NOT attempt to disassemble, repair or modify the device.





Add March Mar


Open the App, select "+" on top right and choose "Switch (Wi-Fi)" to add device.

17



Make sure your smart phone and WiFi+RF switch module are under the same WiFi network at2.4GHz connection. Confirm when the light blinks rapidly (twice a second).

18



The connecting will take about 10–120 seconds to complete depending on your network condition.

19

6

Ende Added successfully Mathematical successfully Dentes added successfully

When pairing is done, the switch will be shown on the App.



Connect to Amazon Alexa or Google Assistant for voice control, or share the devices with your families or friends.

20



9

Enjoy your smart life of home automation for lighting control by using our All-in-one mobile App wherever you are in the world or simply by voice control when you are sitting at home comfortably.

#### Pair and clear up the RF code

#### 1. How to pair the RF code

**1.1 For reset switch**:Press the switch button for 5 times until you hear Di–Di(2 times).Then press the RF transmitter switch for successful pairing.

1.2 For rocker light switch: Press the switch button for 10 times (ON/OFF cycle for 5 times) until you hear Di-Di(2 times). Then press the RF transmitter switch for successful pairing.

1.3 For reset button: Long press the reset button on the switch module for 5 seconds until the beep sounds as Di–Di for 2 times. Then press the RF transmitter switch for successful pairing.

#### 2. How to clear up the RF code

2.1 For reset switch:Press the switch button for 5 times until you hear Di–Di(2 times),waiting for 5 seconds,press the switch button for 5 times again until you hear Di–Di–Di–Di–Di(4 times).Then the RF code is now cleared up.

2.2 For rocker light switch-Press the switch button for 10 times (ON/OFF cycle for 5 times) until you hear Di-Di(2 times), waiting for 5 seconds, press the switch button for 10 times(ON/OFF cycle for 5 times) again until you hear Di-Di-Di(4 times). Then the RF code is now cleared up.

2.3 For reset button:Long press the reset button on the switch module and release your finger until the beep sounds as Di–Di for 2 times.Then press the button after 5 seconds for 5 seconds until the beep sounds as Di–Di–Di–Di for 4 times.

#### 33 How to achieve multi-control association

Note:Please confirm you have successfully finished the WiFi link method above for adding this switch to your Smart Life App before the association.

 WiFi add another smart switch to the same Smart Life/Tuya App.(If there is a smart switch having been added before to the app,just go to next step.)Note:There is no need to wire the new added switch to the light,only L and N are required for wiring.



22

2. Then you will see two devices in the app and click the main switch(as One gang switch as below) by entering into the next operation.

3.Click ∠ in the upper right corner and choose "Multi-Control Association, and then click "+" in the right corner



4.Choose the switch that you want to associate to and then choose the switch button that you want to control the same light.

24

